

KONE KSS 420

# Modernization of elevator signalization

This surface-mounted signalization solution is designed for use in residential and commercial buildings.

## Saving energy

KONE has developed solutions that reduce energy consumption by dimming the signalization in the car at a preset time after the elevator has been used.



## Key Benefits

### Eco-efficient

- Eco-efficient amber colored LED call registration illumination
- Dimming feature when elevator not in use

### Safe

- Increases safety and accessibility of elevator users
- Complies with EN81-70 (European Accessibility Standard)
- Complies with EN81-73 (European Fire Behavior Standard)
- KONE Remote Monitoring for two-way emergency communication with KONE Customer Care Center\*
- Intercom systems\*

### Versatile and stylish

- Serial electrical interface
- Surface mounting with fixed face plate size
- Available satin stainless steel finish
- Landing position indicator available with adjustable arrival gong volumes and text indication fields
- Key fob operation: call or disable elevator remotely\*
- PIN Code locking feature removing the need for key switches\*

\* Optional



Faceplate:  
Asturias Satin stainless steel  
Display: amber-lit  
Floor buttons: max. 14 floors



### Configurations

- Landing hall lantern
- Landing position indicator available with seven segment or dot matrix indicator displays (amber) mounted horizontally
- Car Operating Panel available in two versions, with seven segment or dot matrix display (amber)
- Standard COP devices include: Alarm Button, Door Open Button and Emergency Light
- COP devices can include: Door Close, Key Switches, Braille Marking Tags, KONE Remote Monitoring (KRM) and intercom interface\*
- To comply with EN81-70 max number of car calls per COP = 14

\* Optional

All dimensions are shown in millimeters.

For more information go to [KONE.com](http://KONE.com)